

安装螺栓组件

Mounting Bolt Kits For Modular Valves

叠加阀的安装是用6根双头螺栓(M6x2根、M10x4根)进行连接, 根据回路的构成, 其阀的组合层叠数有变化。因此, 按每种组合层叠数备有其安装螺栓组件。订购安装螺栓组件时, 请按下列表选定螺栓组件号后订购。

■ 型号说明

MBK	-04	-01	-10
系列号	适用叠加阀的规格	螺栓标记	设计号
MBK: 叠加阀螺栓组件	04	01,02,03,04 (参见下面选择表)	10

■ 选择表


螺栓组件号	阀的数量		质量 (一组)g
	电液换向阀 (DSHG-04、52设计号)	叠加阀	
MBK-04-01-10	1	1	0.6
MBK-04-02-10	1	2	0.8
MBK-04-03-10	1	3	1.0
MBK-04-04-10	1	4	1.2

■ 安装尺寸

MBK-04

● 双头螺栓


M6




型号	A	
	M6	M10
MBK-04-01-10	125	140
MBK-04-02-10	195	210
MBK-04-03-10	265	280
MBK-04-04-10	335	350

● 螺母

M6




M10



注) M10双头螺栓使用时, 螺丝长度短的拧进安装面螺丝孔, 螺丝长度长的用在螺母方。
详细请参照04系列叠加阀装配例。

M10



● 螺栓组件构成

M6双头螺栓……4根
M6螺母………4个
M10螺母………2根
M10螺母………2个

● 拧紧扭矩

M6………12~15Nm

M10………45~55Nm

