


CB—B型低压齿轮油泵

CB-B Series Low-pressure Gear Oil Pump

本齿轮泵是将机械能转换为液压能的转换装置，广泛应用于机床，工程机械的液压系统，做为液压系统的动力源，也可作为润滑油泵、输油泵使用。

型号说明



参 数

型 号	额定流量 L/min	额定压力 MPa	额定转速 r/min	容积效率 η v%	总效率 η t%	压力脉动 MPa	噪声值 分贝	驱动功率 Kw	重 量 kg
CB-B6	6	2.5	1450	≧80	≧70		62-75	0.37	3.2
CB-B10	10			≧90	≧81		67-70	0.55	3.5
CB-B16	16							0.82	5.2
CB-B20	20							1.02	5.4
CB-B25	25							1.30	5.5
CB-B32	32							1.65	6.0
CB-B40	40			≧94	≧85		74-77	2.10	10.5
CB-B50	50							2.60	11.0
CB-B63	63							3.30	11.8
CB-B80	80							4.10	17.6
CB-B100	100							5.10	18.7
CB-B125	125			≧95	≧86		80-83	6.50	19.5

技术规格

型 号	C	E	H	C1	C2	D	D1	d	E1	T	b	M	K1	K2
CB-B6	86	90	132	30	35	Φ50	Φ65	Φ16	50	42	5	M8	Z ³ / ₈ "	Z ³ / ₈ "
CB-B10	94												Z ³ / ₄ "	Z ³ / ₄ "
CB-B16	107													
CB-B20	111													
CB-B25	115													
CB-B32	121													
CB-B40	132	102	154	35	40	Φ55	Φ80	Φ22	55	52	6	M8	Z1"	Z ³ / ₄ "
CB-B50	138													
CB-B63	144													
CB-B80	158													
CB-B100	165	121	186	45	50	Φ70	Φ95	Φ30	65	65	8	M8	Z1 ¹ / ₄ "	Z1"
CB-B125	174													

安装尺寸

